

BELOW GROUND SEWER SYSTEM

Main features of RTP below ground sewer system

- Long service life (at least 50 years)
- Good flexibility
- Simple and safe handling and installation,
- Excellent hydraulic performance,
- Excellent shock resistance,
- High wear resistance
- Easy installation
- Environmentally friendly
- All RTP pipes and fittings are SN4 ones

// PP below ground sewer system (sewer laterals)



RTP PIPE

Size DN, (mm)	Wall Thick-ness(mm)	Length, (mm)	Pipes / bundle
110	3,4	500	30
110	3,4	1000	10
110	3,4	2000	10
110	3,4	3000	10
110	3,4	4000	10
110	3,4	5000	10
110	3,4	6000	10
160	4,9	500	4
160	4,9	1000	2
160	4,9	2000	2
160	4,9	3000	2
160	4,9	4000	2
160	4,9	5000	2
160	4,9	6000	2
200	6,2	500	4
200	6,2	1000	2
200	6,2	2000	2
200	6,2	3000	2
200	6,2	4000	2
200	6,2	5000	2
200	6,2	6000	2

PIPE "PIARKOM"

Size DN, (mm)	Wall Thick-ness(mm)	Length, (mm)	Quantity per carton
110	2,7	500	30
110	2,7	1000	10
110	2,7	2000	10
110	2,7	3000	10
110	2,7	4000	10
110	2,7	5000	10
110	2,7	6000	10

CHECK VALVE

Size DN (mm)	Quantity per bag
110	1
160	1



COUPLER

Size DN (mm)	Quantity per bag
110	75
160	20

REPAIR COUPLER

Size DN (mm)	Quantity per bag
110	75
160	20
200	1



TEE

Size DN1/DN2 (mm)	Quantity per bag
110/110 x 45°	18
110/110 x 87°	25
160/110 x 45°	9
160/110 x 87°	9
160/160 x 45°	6
160/160 x 87°	9
200/110 x 45°	1
200/110 x 87°	1
200/160 x 45°	1
200/160 x 87°	1
200/200 x 45°	1
200/200 x 87°	1



CLEAN OUTS

Size DN (mm)	Quantity per bag
110	25
160/110	9
160	9
200	1



ELBOW

Size DN1 (mm)	Quantity per bag
110 x 15°	70
110 x 30°	50
110 x 45°	50
110 x 67°	50
110 x 87°	40
160 x 15°	1
160 x 30°	1
160 x 45°	18
160 x 67°	1
160 x 87°	12
200 x 30°	1
200 x 45°	10
200 x 87°	8



DOUBLE Y

Size DN1/DN2/DN3 (mm)	Quantity per bag
110/110/110 x 45°	14
110/110/110 x 87°	18
110/110/110 x 87° two-plane cross	18



REDUCER

Size DN (mm)	Quantity per bag
160/110	40
200/110	1
200/160	20



END CAP

Size DN (mm)	Quantity per bag
110	250
160	100
200	40