

SEWER PIPE SYSTEM

Main features of RTP pipes

- ▶ Long service life (at least 50 years)
- ▶ Simple and safe handling and installation
- ▶ Excellent hydraulic performance
- ▶ Excellent mechanical features at high temperatures
- ▶ High resistance to temperature changes (the pipes are resistant to temperature spikes up to 95 °C)
- ▶ High wear resistance
- ▶ Preinstalled rubber seals
- ▶ Only high quality virgin raw materials of leading plastic producers (Borealis, Lyondellbasell, Sibur) are used in production
- ▶ Wide product range (incl. exclusive fittings)
- ▶ Tried and tested reliable seal

// PP sewer pipes system



MOL DD lip seal ring with reinforcing PP ring



- ▶ The outstanding long-term elasticity of the rubber seal ensures a durable sealing effect
- ▶ The highest possible safety and reliability
- ▶ The seal is not pushed out when the pipes are laid
- ▶ Excellent connecting properties
- ▶ Firm fit in the socket



RTP PIPE (EN1451)

Size DN (mm)	Wall Thickness (mm)	Length (mm)	Pipes / bundle
32	1,8	150	350
32	1,8	250	250
32	1,8	500	150
32	1,8	750	10
32	1,8	1000	10
32	1,8	1500	10
32	1,8	2000	10
40	1,8	150	250
40	1,8	250	150
40	1,8	500	80
40	1,8	750	10
40	1,8	1000	10
40	1,8	1500	10
40	1,8	2000	10

Size DN (mm)	Wall Thickness (mm)	Length (mm)	Pipes / bundle
50	1,8	150	150
50	1,8	250	100
50	1,8	500	60
50	1,8	750	10
50	1,8	1000	10
50	1,8	1500	10
50	1,8	2000	10
50	1,8	3000	10
110	2,7	150	60
110	2,7	250	50
110	2,7	500	30
110	2,7	750	20
110	2,7	1000	10
110	2,7	1500	10
110	2,7	2000	10
110	2,7	3000	10

PIPE "PIARKOM"

Size DN (mm)	Wall Thickness (mm)	Length (mm)	Pipes / bundle
50	1,5	150	150
50	1,5	250	100
50	1,5	500	60
50	1,5	750	10
50	1,5	1000	10
50	1,5	1500	10
50	1,5	2000	10
50	1,5	3000	10
110	2,2	150	60
110	2,2	250	50
110	2,2	500	30
110	2,2	750	20
110	2,2	1000	10
110	2,2	1500	10
110	2,2	2000	10
110	2,2	3000	10